



- 1 On/Off switch   2 Input Voltage Display   3 Output Voltage Display   4 Start Up Delay time selector stabilization function: Delay 3 minutes, Undelay 10 seconds
- 5 Input Voltage range selector   6 Led Power - AVR - Overvoltage/undervoltage   7 AC input cable   8 Stabilized output socket   9 Input socket

**Main Specifications**

- Domestic users, Lighting Systems, Industrial Processes, Communications, Electromedical equipment
- High stabilization speed
- High Efficiency
- No brownouts stabilization
- Do not introduce harmonic distortion
- Management changes from 0 to 100% load

**Specifications**

Model	STABILIZER POWER REG 2.000-3.000	
Code	FSTELPRE2000M	FSTELPRE3000M
Nominal Power	2.000 VA	3.000 VA
Active Power	1.600 W	2.400 W
Power Factor	0,8	
Technology	Electronic stabilization	
Start Up Delay time selector stabilization function	Selectable 3 minutes-10 seconds	
Dimension WxHxD	13x18x24 cm	15x20x30 cm
Dimension (with packing) WxHxD	19x24x39 cm	23x27x33 cm
Weight	6,6Kg	8,6 Kg
<b>Input</b>		
Number of phases	1Ph+N	
Nominal voltage	230Vac	
Input voltage range	110Vac-280Vac o 150Vac-270Vac (selectable)	
Nominal frequency	50/60 Hz	
<b>Output</b>		
Number of phases	1Ph+N	
Nominal voltage	230Vac	
Voltage regulation	±6%	
Nominal frequency	50/60 Hz	
<b>Environmental specification</b>		
Working temperature	From 0 to 55 °C	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE	

© 2020 Tecnoware Power Systems. The technical data may change without prior notice.