



Rated operational voltage U _e V	Modules Number	Color	Part no. Article no.	Price See price list	Std. pack	Information relevant for export to North America
Complete units						
Base module with foot and 100 mm tube including filament lamp Continuous light, IP54						
24 V AC/DC	3		SL-100-L-RYG/24 205352		1 off 	Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified Degree of Protection UL/CSA Type 12, with additional SL-IP65: part no. 4X
24 V AC/DC	2		SL-100-L-RG/24 205354		1 off 	Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified Degree of Protection UL/CSA Type 12, with additional SL-IP65: part no. 4X
Customized complete unit						
To order use form F0315, → Data sheet in Online Catalog * = Freely selectable customer identification or stock no.; Maximum 10 characters						
-	-	-	SL-COMBINATION-* 229655		1 off 	Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified

Terminal type	Part no. Article no.	Price See price list	Std. pack	Notes	Information relevant for export to North America
Base module					
Black, with cover					
Screw terminals	SL-B 205311		1 off 	-	Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified
Cage clamp Cage clamp is a registered trademark of Wago Kontakttechnik GmbH, Minden,	SL-CB 218483		1 off 		Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified
Connection to AS-Interface	SL-B-ASI 222174		1 off	Base module (printed circuit board in base enclosure with 3 outputs): <ul style="list-style-type: none"> Total power supply from AS-Interface (max. 250 mA) using 2-way screw terminal Combination of 3 surface mounting modules with different functions (continuous, flashing, strobe light and acoustic indication) Status indication via LEDs Order stacking modules separately 	
Continuous light module					
Without light elements, filament lamps → Page 2/107, LED → Page 2/107					
	SL-L-W 205312		1 off 		Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking E29184 UL File No. E29184 UL CCN NKCR CSA File No. 012528 CSA Class No. 3211-03 NA Certification UL Listed, CSA certified
	SL-L-R 205313				
	SL-L-G 205314				
	SL-L-Y 205315				
	SL-L-B 205316				