

**Articolo**

**522.1653**  
 PRESA PAR.C/DIR.2P+T 16A 44 6H

**Immagine****Anagrafica**

Minimo ordinabile	10 NR
Peso Netto	0.194 KG
Codice EAN	8001636072654
Codice INTRASTAT	85366990

**TechData**

Descrizione sintetica	PRESA PARETE
Grado di protezione	IP44/IP54
Serie commerciale	Serie OPTIMA
Tipo di uscite disponibili	DIRITTA
Morsetti	Morsetti a vite
Uscita cavo	CENTRINO DI FORATURA
Corrente nominale	16A
Poli	2P+T
Frequenza d'impiego	50Hz
Frequenza d'impiego	60Hz
Tensione nominale	200-250V
Colore	BLU
Riferimento Orario	6h

**Marchi e Certificazioni**

UE  
 Dichiarazione di conformità



I.M.Q. - ENEC 03  
 European Norms Electrical Certification



CCC (China)  
 China Compulsory Certification mark

**Norme e Leggi**

EN 60309-2 (1999)  
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)  
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

### Packaging

Descrizione	Cartone
Quantità	
Codice EAN	8001636887494
Peso lordo	11,35 KG
Volume	66990 CCM
Dimensioni	385x580x300 (MM)
Descrizione	Scatola
Quantità	10
Codice EAN	8001636887500
Peso lordo	2,27 KG
Volume	9450,54 CCM
Dimensioni	258x333x110 (MM)

### Allegati



Disegno tecnico [DWG]

.dwg



Disegno tecnico [PDF]

.pdf



Disegno tecnico [STP]

.stp

### Note:



Parete liscia con centrino per foratura



Passacavo in gomma incluso

