


Item Code: 1111LI4-6

Product description: LI 4-6 ACCUMULATORE 6V 4Ah




● **Outer dimensions (mm)**



● **Specifications**

Nominal Voltage		6V
Rated capacity (20 hour rate)		4.0 Ah
Dimensions	Total Height	106 mm(4.17 inches)
	Height	101 mm(3.98 inches)
	Length	70 mm(2.76 inches)
	Width	47 mm(1.85 inches)
Weight Approx		0.72 Kg(1.59 lbs)


● **Terminal Type (mm)**



● **Characteristics**

Capacity 25 °C(77 °F)	20 hour rate (0.20A)	4.00 AH
	10 hour rate (0.37A)	3.70 AH
	5 hour rate (0.68A)	3.40 AH
	1 hour rate (2.40A)	2.40 AH
	1.5 hour discharge to 5.25 V	1.6 A
Internal Resistance	Full charged Battery at 25 °C(77 °F)	34 m Ω
Capacity affected by Temperature (20hour rate)	40 °C(104 °F)	102%
	25 °C(77 °F)	100%
	0 °C(32 °F)	85%
	-15 °C(5 °F)	65%
Self-Discharge at 25 °C(77 °F)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Terminal	T1	
Charge (constant Voltage)	Cycle	Initial Charging Current less than 1.6A Voltage 7.20-7.35V
	Float	Voltage 6.75-6.90 V

● **Discharge Curves 25 °C(77 °F)**



Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25 °C(77 °F)													
Time		5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
4.80V	A	14.4	9.02	7.00	4.60	2.40	1.40	1.03	0.83	0.70	0.46	0.38	0.21
	W	84.9	53.3	40.3	24.4	13.8	8.1	6.0	4.8	4.1	2.7	2.2	1.20
5.10V	A	13.2	8.83	6.43	4.37	2.25	1.34	1.00	0.80	0.69	0.46	0.37	0.20
	W	79.9	52.5	37.9	24.3	13.0	7.8	5.8	4.6	4.0	2.6	2.2	1.17
5.25V	A	12.2	8.44	6.00	4.23	2.18	1.32	0.98	0.76	0.68	0.45	0.37	0.20
	W	77.2	49.0	36.3	24.0	12.6	7.6	5.7	4.4	4.0	2.6	2.1	1.16
5.40V	A	11.1	8.07	5.60	4.04	2.11	1.28	0.97	0.75	0.65	0.44	0.36	0.20
	W	73.7	47.5	34.9	23.9	12.3	7.5	5.6	4.3	3.8	2.5	2.1	1.13
5.55V	A	9.64	7.60	5.20	3.76	2.03	1.25	0.92	0.73	0.62	0.43	0.35	0.19
	W	57.4	45.9	33.3	23.8	12.1	7.4	5.5	4.3	3.7	2.4	2.0	1.13



ISO 14001: 2004
Sistema di gestione ambientale



CI ITPI: 2015
100% Made in Italy
Certificate



ISO 9001: 2008
Sistema di gestione della qualità



OHSAS 18001: 2007
Sistema di gestione per la salute e sicurezza sul lavoro

LINCE ITALIA S.p.A.

Via Variante di Cancelliera s.n.c., Ariccia (RM) Italia
Tel.: +39 06/09301801 - Fax: +39 06/0930180233

www.lincede.net - info@lincede.net
MD-03.11 Rev. 3 - Pag.: 1 di 1